

F1 F1R F1-PLUS

Case Fan



Features:

- Multi-color LED fan
- Hydraulic bearing fan for durability and silent operation



SPECIFICATIONS

PART NUMBER	F1-BK-3P F1-WH-3P	F1-BK-4P F1-WH-4P
CONNECTOR	3-pin	4-pin
MODEL	DF1202512SELN	
AIRFLOW DIRECTION	Standard	
DIMENSION (L x W x H)	120 x 120 x 25 mm	
FAN RATED VOLTAGE	DC 12V	
FAN RATED CURRENT	0.25 A \pm 10%	
FAN RATED POWER	3 W \pm 10%	
FAN LEAVES	9	
CABLE LENGTH	500 mm \pm 10%	
BEARING	Hydraulic bearing	
MAX AIRFLOW	38.98 CFM	
STATIC PRESSURE	0.59 mm-H ₂ O	
SPEED	1100 \pm 10% RPM	
NOISE LEVEL	\leq 21.97 dB(A) @ 300 mm	
LED TYPE	Multi-color	

SPECIFICATIONS

PART NUMBER	F1R-BK-3P F1R-WH-3P	F1R-BK-4P F1R-WH-4P
CONNECTOR	3-pin	4-pin
MODEL	DF1202512SELN	
AIRFLOW DIRECTION	Reverse	
DIMENSION (L x W x H)	120 x 120 x 25 mm	
FAN RATED VOLTAGE	DC 12V	
FAN RATED CURRENT	0.25 A ± 10%	
FAN RATED POWER	3 W ± 10%	
FAN LEAVES	9	
CABLE LENGTH	500 mm ± 10%	
BEARING	Hydraulic bearing	
MAX AIRFLOW	38.98 CFM	
STATIC PRESSURE	0.59 mm-H ₂ O	
SPEED	1100 ± 10% RPM	
NOISE LEVEL	≤ 21.97 dB(A) @ 300 mm	
LED TYPE	Multi-color	

SPECIFICATIONS

PART NUMBER	F1-PLUS-BK-3P F1-PLUS-WH-3P	F1-PLUS-BK-4P F1-PLUS-WH-4P
CONNECTOR	3-pin	4-pin
MODEL	DF1402512SELN	
AIRFLOW DIRECTION	Standard	
DIMENSION (L x W x H)	140 x 140 x 25 mm	
FAN RATED VOLTAGE	DC 12V	
FAN RATED CURRENT	0.28 A ± 10%	
FAN RATED POWER	3.36 W ± 10%	
FAN LEAVES	9	
CABLE LENGTH	500 mm ± 10%	
BEARING	Hydraulic bearing	
MAX AIRFLOW	46.69 CFM	
STATIC PRESSURE	0.47 mm-H ₂ O	
SPEED	900 ± 10% RPM	
NOISE LEVEL	≤ 21 dB(A) @ 300 mm	
LED TYPE	Multi-color	