

FA7 FA7R

Case Cooling Fan



Features:

- Support aRGB Sync
- Brilliant aRGB glow flowing smoothly over every blade
- Nine blades, aerodynamic-orientated fan design
- Durable hydraulic bearing for long-lasting, quiet operation
- Standard 4-pin PWM and 3-pin ARGB connectivity for broad compatibility with popular motherboards and controllers
- Ideal as intake or exhaust in side, front, or top positions to improve overall case airflow and system stability



CASE FAN
FA7 / FA7R
V251202K

REVISION HISTORY

Version Number	Modification Description	Modified By
-----------------------	---------------------------------	--------------------

SPECIFICATIONS

PART NUMBER	FA7-BK / FA7-WH
MODEL	FA7
AIRFLOW DIRECTION	STANDARD
CONNECTOR	4-pin (PWM) + 3-pin (ARGB)
DIMENSION (L x W x H)	120 x 120 x 25 mm
FAN RATED VOLTAGE	DC 12 V
FAN RATED CURRENT	0.20 A
FAN RATED POWER	2.4 W
FAN LEAVES	9
CABLE LENGTH	500 mm ± 10%
BEARING	Hydraulic bearing
MAX AIRFLOW	47 CFM
STATIC PRESSURE	0.98 mm-H ₂ O
SPEED	600 - 1400 RPM ± 10 %
NOISE LEVEL	≤ 23.4 dB(A)
LED TYPE	aRGB
LED VOLTAGE	5 V
LED CURRENT	0.22 A
LED MAX. POWER	1.1 W

SPECIFICATIONS

PART NUMBER	FA7R-BK / FA7R-WH
MODEL	FA7R
AIRFLOW DIRECTION	Reversed
CONNECTOR	4-pin (PWM) + 3-pin (ARGB)
DIMENSION (L x W x H)	120 x 120 x 25 mm
FAN RATED VOLTAGE	DC 12 V
FAN RATED CURRENT	0.20 A
FAN RATED POWER	2.4 W
FAN LEAVES	9
CABLE LENGTH	500 mm ± 10%
BEARING	Hydraulic bearing
MAX AIRFLOW	47 CFM
STATIC PRESSURE	0.98 mm-H ₂ O
SPEED	600 - 1400 RPM ± 10 %
NOISE LEVEL	≤ 23.4 dB(A)
LED TYPE	aRGB
LED VOLTAGE	5 V
LED CURRENT	0.22 A
LED MAX. POWER	1.1 W

PICTURES



PICTURES

