

FC7 FC7R

Case Fan



Features:

- Infinite mirror design on the side
- ARGB sync creating a mesmerizing visual effect
- PWM intelligent speed control
- Hydraulic bearing fan for durability and silent operation



CASE FAN
FC7 / FC7R
VER250225BN

SPECIFICATIONS

PART NUMBER	FC7-BK / FC7-BK-1IN1 FC7-WH / FC7-WH-1IN1
CONNECTOR	4-pin (PWM) + 3-pin (ARGB)
MODEL	DF1202512SELN
AIRFLOW DIRECTION	Standard
DIMENSION (L x W x H)	120 x 120 x 25 mm
FAN RATED VOLTAGE	DC 12V
FAN RATED CURRENT	0.22 A \pm 10%
FAN RATED POWER	2.64 W \pm 10%
FAN LEAVES	9
CABLE LENGTH	500 mm \pm 10%
BEARING	Hydraulic bearing
MAX AIRFLOW	47.65 CFM
STATIC PRESSURE	1.59 mm-H ₂ O
SPEED	600 - 1800 \pm 10% RPM
NOISE LEVEL	\leq 52.2 dB(A) @ 300 mm
LED TYPE	aRGB
LED VOLTAGE	5V
LED CURRENT	0.72 A \pm 10%
LED MAX. POWER	3.6 W \pm 10%

SPECIFICATIONS

PART NUMBER	FC7R-BK / FC7R-BK-1IN1 FC7R-WH / FC7R-WH-1IN1
CONNECTOR	4-pin (PWM) + 3-pin (ARGB)
MODEL	DF1202512SELN
AIRFLOW DIRECTION	Reverse
DIMENSION (L x W x H)	120 x 120 x 25 mm
FAN RATED VOLTAGE	DC 12V
FAN RATED CURRENT	0.22 A \pm 10%
FAN RATED POWER	2.64 W \pm 10%
FAN LEAVES	9
CABLE LENGTH	500 mm \pm 10%
BEARING	Hydraulic bearing
MAX AIRFLOW	43.65 CFM
STATIC PRESSURE	1.12 mm-H ₂ O
SPEED	600 - 1800 \pm 10% RPM
NOISE LEVEL	\leq 47.14 dB(A) @ 300 mm
LED TYPE	aRGB
LED VOLTAGE	5V
LED CURRENT	0.58 A \pm 10%
LED MAX. POWER	2.9 W \pm 10%

PICTURES

