

FN7 FN7R

Case Fan



Features:

- 600-1800 RPM allows precise speed control
- PWM temperature control efficiently adjusts temperature
- 7-blade design provides stronger airflow
- ARGB sync creating a mesmerizing visual effect



CASE FAN
FN7 / FN7R
VER250623BN

REVISION HISTORY

Version Number	Date	Modification Description	Modified By
VER250530BN	May 30, 2025	Updated Model	Ben
VER250604BN	Jun 4, 2025	Updated Bearing	Ben
VER250623BN	Jun 23, 2025	Updated Specifications	Ben

SPECIFICATIONS

PART NUMBER	FN7-BK / FN7-WH
CONNECTOR	4-pin (PWM) + 3-pin (ARGB)
MODEL	FN7
DIMENSION (L x W x H)	120 x 120 x 25 mm
FAN RATED VOLTAGE	DC 12V
FAN RATED CURRENT	0.11 A \pm 10%
FAN RATED POWER	1.32 W \pm 10%
FAN LEAVES	7
CABLE LENGTH	500 mm \pm 10%
BEARING	Hydraulic bearing
MAX AIRFLOW	39.4 CFM
STATIC PRESSURE	1.14 mm-H ₂ O
SPEED	600 - 1800 \pm 10% RPM
NOISE LEVEL	\leq 28.95 dB(A)
LED TYPE	aRGB
LED VOLTAGE	5V
LED CURRENT	0.342 A \pm 10%
LED MAX. POWER	n/a

SPECIFICATIONS

PART NUMBER	FN7R-BK / FN7R-WH
CONNECTOR	4-pin (PWM) + 3-pin (ARGB)
MODEL	FN7R
DIMENSION (L x W x H)	120 x 120 x 25 mm
FAN RATED VOLTAGE	DC 12V
FAN RATED CURRENT	0.11 A ± 10%
FAN RATED POWER	1.32 W ± 10%
FAN LEAVES	7
CABLE LENGTH	500 mm ± 10%
BEARING	Hydraulic bearing
MAX AIRFLOW	38.39 CFM
STATIC PRESSURE	1.14 mm-H ₂ O
SPEED	600 - 1800 ± 10% RPM
NOISE LEVEL	≤ 31.278 dB(A)
LED TYPE	aRGB
LED VOLTAGE	5V
LED CURRENT	0.342 A ± 10%
LED MAX. POWER	n/a

PICTURES

