

XF7 XF7R

Case Fan



Features:

- Made for both PC case cooling and radiator compatibility, providing flexible installation options
- Eye-catching infinite mirror design adds depth and elegance, creating a mesmerizing visual effect
- Support aRGB sync
- Interlocking mechanism allows fans to connect seamlessly, enabling a clean, streamlined setup with only one cable needed for power and ARGB sync
- Fluid Dynamic Bearing (FDB) fan for longer lifespan, smoother rotation, and quieter operation



CASE FAN
XF7 / XF7R

VER250823KN

SPECIFICATIONS

MODEL	XF7
DIMENSION (L x W x H)	120 x 120 x 25 mm
AIRFLOW DIRECTION	Standard
FAN RATED VOLTAGE	DC 12V
FAN RATED CURRENT	0.13 A \pm 10%
FAN RATED POWER	1.56W \pm 10%
FAN BLADE	9
BEARING	FDB
MAX AIR FLOW	56.8 CFM
STATIC PRESSURE	2.2 mm-H ₂ O
SPEED	600-2000 \pm 10% RPM
NOISE LEVEL	\leq 33.12 dB(A)
LED TYPE	aRGB
LED VOLTAGE	5V
LED CURRENT	0.225 A \pm 20%
LED MAX. POWER	1.125W
CONNECTOR	4-pin (PWM) female and male connectors for daisy chain 3-pin (ARGB) female and male connectors for daisy chain 6-pin (Interlocking) female and male connectors for daisy chain

SPECIFICATIONS

MODEL	XF7R
DIMENSION (L x W x H)	120 x 120 x 25 mm
AIRFLOW DIRECTION	Reverse
FAN RATED VOLTAGE	DC 12V
FAN RATED CURRENT	0.15 A \pm 10%
FAN RATED POWER	1.80W \pm 10%
FAN BLADE	9
BEARING	FDB
MAX AIR FLOW	58.28 CFM
STATIC PRESSURE	1.81 mm-H ₂ O
SPEED	700-2000 \pm 10% RPM
NOISE LEVEL	\leq 35.911 dB(A)
LED TYPE	aRGB
LED VOLTAGE	5V
LED CURRENT	0.385 A \pm 20%
LED MAX. POWER	1.925W
CONNECTOR	4-pin (PWM) female and male connectors for daisy chain 3-pin (ARGB) female and male connectors for daisy chain 6-pin (Interlocking) female and male connectors for daisy chain

PICTURES

